



Vapor Tightness Form

Reinauer Transportation Companies, LLC.
 1983 Richmond Terrace
 Staten Island, NY 10302 USA
 (718) 816-8167 www.Reinauer.com

Barge Name: RTC 107 Official No.: 1252825 Date of Test: 4/26/24

Test Type: AIR Pressure: 41.5 in Testing Location: SMRY North Kingstown, RI

Compartment ID	Total Volume of Product Tank bbls (V)	Lowest PVR setting (in. of H ₂ O) [P(l)]	Max Permitted Ldg. rate (bbls/hr) [L]	Type of Air Dry/Inert	Date PRV Pressure obtained	Test Pressure "P" (In. of H ₂ O)	Amount of Drop "D" (In. of H ₂ O)	Pressure Reading after 30 min. (in. of H ₂ O) [P(f)]	Pia= P(i)/27.7	P=P(i)-P(f)	PM=0.861 * Pia * L/V	If P≤PM, vessels tight
Sample	20,000	41.5	12,000	Inert	8 / 20 / 10	41.5	0.7	40.8	1.5	.7	0.77	Tight
1P	9683	41.5	15500	Dry		41.5	1.5	40.0	1.5	1.5	1.82	Tight
1S	9683	41.5	15500	Dry		41.5	1.5	40.0	1.5	1.5	1.82	Tight
2P	11120	41.5	15500	Dry		41.5	1.5	40.0	1.5	1.5	1.80	Tight
2S	11120	41.5	15500	Dry		41.5	1.5	40.0	1.5	1.5	1.80	Tight
3P	11120	41.5	15500	Dry		41.5	1.5	40.0	1.5	1.5	1.80	Tight
3S	11120	41.5	15500	Dry		41.5	1.5	40.0	1.5	1.5	1.80	Tight
4P	11120	41.5	15500	Dry		41.5	1.5	40.0	1.5	1.5	1.80	Tight
4S	11120	41.5	15500	Dry		41.5	1.5	40.0	1.5	1.5	1.80	Tight
5P	10952	41.5	15500	Dry		41.5	1.5	40.0	1.5	1.5	1.83	Tight
5S	10952	41.5	15500	Dry		41.5	1.5	40.0	1.5	1.5	1.83	Tight

Load Rate BBLs / HR	PV Settings Pressure		PV Setting Vacuum		Pressure Drop	Max Input Voltage	Max Input Current	Total Connected Inductance	Total Conducted Capacitance
	100 %	80 %	100 %	80 %					
15500	2.90	2.0	.51	.50	.83	20.66VDC	155mA	0.6mH	0.18uF

List any leaks found or repairs made during annual vapor-tightness testing: _____

I certify that this vessel is vapor tight as required by 40 CFR 63.565 (c) (1) or EPA Method 21.

Name of Tester: George Gardner Tester's Signature: George Gardner

Tester's Title: SMRY Manager Tester's Certification: _____

Witness if any: Ben Mantey ABS Witness's Signature: Ben Mantey